

CLR | multi slide

Performance - Minimal Frame



The CLR | multi-slide is our premium European engineered, thermally broken, minimal frame - maximum view sliding door series. The CLR | multi slide features various track configurations, stainless steel hardware, triple pane glazing, an integrated handle and a 1" (26mm) stile that allows for an unobstructed view. This system is the perfect solution for areas where thermal, air, water and structural values are a critical factor. The panels neatly slide away, allowing for a unified space in the indoors or out.

- Application** Patios, verandas, balconies, bars, greenhouses, restaurants, hotels, shopping malls, pool areas, hot tub surrounds, etc.
- Thermal** The profiles on the CLR | multi slide are composed of 6060 aluminum. The thermal break within the aluminum profiles are composed of 1-5/8" (42 mm) polyimide bars, which provides excellent insulation.
- Dimensions** Made-to-measure door panels for openings up to 144" (3658mm) in height. The CLR | multi slide system spans widths up to 590-1/2" (15000mm) with various multi-panel configurations to choose from.
- Sliding** The CLR | multi slide is a bottom weighted system that runs on a bottom track with stainless steel wheel assemblies. Every door panel has adjustable wheel assemblies for perfect alignment.
- Closure** The CLR | multi slide features an integrated flush mount handle design that is built into the door frame. The integrated handle is available with a key lock.
- Features** The CLR | multi slide's lower track performs flawlessly when faced with heavy rain and high winds, while only being 7/8" (23mm) high. To increase the systems weather performance even further, an optional discharge reservoir or drain pan can be installed under the bottom track. The CLR | multi slide's panel frame is a minimal 1" (26mm) wide to allow for an unmatched sleek and contemporary look.

Specifications

Operation	Bottom Weighted
Thermally Broken	Yes
Max Panel Weight	661lbs (300kg)
Standard Glazing	1-7/8" (48mm) IGU
Triple Pane Specs.	1-7/8" (48mm)
Max Panel Width	*Configuration Specific
Max System Width	590-1/2" (15,000mm)
Max System Height	144" (3658mm) <small>*Restrictions Apply. Maximum panel size is limited to 661 lbs (300kg)</small>

Color Options

Standard Colors	Clear Anodized
	RAL 9006 White Aluminum
	RAL 9010 Pure White
	RAL 9016 White
	RAL 1013 Linen
	RAL 8017 Brown
Custom Colors	RAL 7035 Light Grey
	Please contact for quote
Hardware Colors	Silver <small>*Hardware includes handles and locks</small>

CLR | multi slide

Options

Bottom Threshold Options	High Performance Discharge Reservoir
Lock Options	Integrated Handle with Key Lock

Delivery

Standard 8-12 week delivery
FOB: Surrey, BC, Canada
Freight to be quoted

